

## CLAIMS

1. Water modifier characterized in that it comprises fired earthy substance that contains at least one of  $\text{Al}_2\text{O}_3$ ,  $\text{B}_2\text{O}_3$ ,  $\text{BaO}$ ,  $\text{CaO}$ ,  $\text{Fe}_2\text{O}_3$ ,  $\text{K}_2\text{O}$ ,  $\text{MgO}$ ,  
5  $\text{MnO}$ ,  $\text{Na}_2\text{O}$ ,  $\text{SiO}_2$ ,  $\text{TiO}_2$  and  $\text{ZnO}$ .

2. Water modifier characterized in that it comprises earthy substance that contains aluminium, boron, barium, calcium, iron, kalium, magnesium, manganese, sodium, silicon, titanium or zinc, or a compound containing these  
10 elements in an unfired state, and contains at least one of  $\text{Al}_2\text{O}_3$ ,  $\text{B}_2\text{O}_3$ ,  $\text{BaO}$ ,  $\text{CaO}$ ,  $\text{Fe}_2\text{O}_3$ ,  $\text{K}_2\text{O}$ ,  $\text{MgO}$ ,  $\text{MnO}$ ,  $\text{Na}_2\text{O}$ ,  $\text{SiO}_2$ ,  $\text{TiO}_2$  and  $\text{ZnO}$  in a fired state.

3. Water modifier characterized in that it comprises fired earthy substance that contains 5-20 wt.% of aluminium, 0.05-0.5 wt.% of boron, 0.01-0.1  
15 wt.% of barium, 0.5-3 wt.% of calcium, 1-5 wt.% of iron, 0.5-3 wt.% of kalium, 0.1-1 wt.% of magnesium, 0.01-0.1 wt.% of manganese, 0.1-1 wt.% of sodium, 20-50 wt.% of silicon, 0.05-0.5 wt.% of titanium and 0.005-0.05 wt.% of zinc according to quantitative analysis by high-frequency inductively coupled plasma emission spectrometry (ICP).

20

4. Modified water characterized in that it is obtained by the treatment with any one of the water modifiers of claims 1-3.

5. Modified water characterized in that it is obtained by making water  
25 through any one of the water modifiers of claims 1-3.

6. Coolant characterized in that it is obtained by mixing any of the

modified water of claims 4 and 5 with antifreeze.

7. Coolant according to claim 6, wherein the coolant contains 1-50% of the modified water and 50-99% of the antifreeze.

5

8. A method of producing coolant characterized in that it comprises mixing the modified water of any one of claims 4 and 5 with antifreeze.

9. A method of producing coolant according to claim 8, wherein the  
10 modified water of any one of claims 4 and 5 is mixed with antifreeze, and then the  
mixture is allowed to flow again through the water modifier of any one of claims  
1-3.